

IP68



- window size  $\Phi 75\text{mm}$
- Inside size  $\Phi 100 \times 300\text{mm}$
- ATEX Zone 1&2 / 21&22
- 200-degree high temperature Housing
- Double-layer structure, water & wind cold
- Made of 304 stainless steel material (316,316L for optional)

## EX Marking




## Certification



## Markets



	<b>Ex-Level</b>	<b>ATEX</b>
	<b>Ingress Protection level</b>	<b>IP68</b>
<b>Specification</b>	<b>Max Temperature of Windows</b>	<b>≤150°C</b>
	<b>Relative humidity</b>	<b>≤ 95% (+25°C)</b>
	<b>pressured air temperature</b>	<b>≤30°C</b>
	<b>Air pressure</b>	<b>0.1~0.3Mpa</b>
	<b>Air flow rate</b>	<b>0.1~0.3m3/min</b>
	<b>Atmospheric pressure</b>	<b>80kpa~106 kpa</b>
	<b>Thermostat System</b>	<b>optional</b>
	<b>Supply voltage</b>	<b>DC12V /AC220V (optional )</b>
	<b>Suitable Environment</b>	<b>Apply to explosive gas and combustibile dust environment</b>
	<b>Material</b>	<b>304 stainless steel</b>
	<b>inlet interface specifications</b>	<b>G1/4 for air cooling, G1/2" x 2 for output cable</b>
	<b>External dimensions</b>	<b>350x140x160mm</b>
	<b>inside dimension</b>	<b>Φ100mm*300mm (length )</b>
	<b>Windows area</b>	<b>Φ60</b>
<b>Installation method</b>	<b>PTZ, Wall Hanging dyadic, fixed bracket, Pillar base</b>	



**WV-U1132A**  
**WV-U1142A**



[WV-U1132A Product Data Sheet](#)  
[WV-U1142A Product Data Sheet](#)



**WV-S1132**  
**WV-S1136A**



[WV-S1132 Product Data Sheet](#)  
[WV-S1136A Product Data Sheet](#)



**NBN-73023-BA**



[NBN-73023-BA Product Data Sheet](#)

**VT-B02**  
Bracket for B series



**VT-B04**  
Bracket for B series



**VT-B03**  
Bracket for B series

