

IP68



- Window size: $\Phi 75\text{mm}$
- ATEX Zone 1&2 / 21&22
- Inside size: $\Phi 100 \times 300\text{mm}$
- Made of 304 stainless steel material (316, 316L for optional)
- 250-degree high temperature Housing
Double-layer structure, water & wind cold

EX Marking




Certification



Markets



	Ex-Level	ATEX
	Ingress Protection level	IP68
specifications	Working temperature	-40°C~60°C
	cooling water temperature	≤30°C
	Cooling water flow	0.3~0.4m3/h
	the working cooling water	0.1~0.2Mpa
	pressured air temperature	≤30°C
	Air pressure	0.1~0.3Mpa
	air flow rate	0.1~0.2m3/min
	Relative humidity	≤ 95% (+25°C)
	Atmospheric pressure	80kpa~106 kpa
	Supply voltage	DC12V /AC220V (optional)
	Material	304 stainless steel
	Inlet interface specifications	G1/4 for air and water cooling, G1/2" x 2 for output cable
	External dimensions	351.5x140x182.5mm
	Inside dimension	Φ100mm*300mm (length)
	Windows area	Φ60
Installation method	PTZ, Wall Hanging dyadic, fixed bracket, Pillar base	



WV-U1132A
WV-U1142A



[WV-U1132A Product Data Sheet](#)
[WV-U1142A Product Data Sheet](#)



WV-S1132
WV-S1136A



[WV-S1132 Product Data Sheet](#)
[WV-S1136A Product Data Sheet](#)



NBN-73023-BA



[NBN-73023-BA Product Data Sheet](#)

VT-B02
Bracket for B series



VT-B04
Bracket for B series



VT-B03
Bracket for B series

