

IP68



- window size: $\Phi 60\text{mm}$
- ATEX Zone 1&2 / 21&22
- Inside size: $\Phi 100 \times 290\text{mm}$
- Made of 304 stainless steel material (316,316L for optional)
- Usual power supply: AC220V/DC12V, other Power mode can be customized
- Class I Division 1&2 / Class II Division 1&2 and all the rest except zone 0
- Fixed focus or zoom camera can be loaded

EX Marking




Certification



Markets



	Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db
	Ingress Protection level	IP68
specifications	Temperature range	-40°C~60°C
	Relative humidity	≤ 95% (+25°C)
	Atmospheric pressure	80kpa~106 kpa
	Thermostat System	Optional
	Supply voltage	DC12V /AC220V (optional)
	Material	304 stainless steel (316, 316L for optional)
	Inlet interface specifications	2pcs M25*1.5 output (original G3/4)
	Inside dimension	Φ100mm*290mm (length)
	Windows area	Φ60
	Applicable environment	Apply to explosive gas and combustible dust environment
	Installation method	PTZ, Wall Hanging dyadic, fixed bracket, Pillar base



WV-U1132A
WV-U1142A



[WV-U1132A Product Data Sheet](#)
[WV-U1142A Product Data Sheet](#)



WV-S1132
WV-S1136A



[WV-S1132 Product Data Sheet](#)
[WV-S1136A Product Data Sheet](#)



NBN-73023-BA



[NBN-73023-BA Product Data Sheet](#)

VT-B02
Bracket for B series



VT-B04
Bracket for B series



VT-B03
Bracket for B series

