

IP68



- ATEX Zone 1&2 / 21&22
- Supply voltage: AC85V-260V
- Smart windshield wiper optional
- Suitable for thermal & day camera dual-sensor
- Made of 304 stainless steel material (316,316L for optional)
- horizontal 360° (Endless) , Vertical : ±90° , Rotate speed 0.1°/S~40°/s
- Class I Division 1&2 / Class II Division 1&2 and all the rest except zone 0
- The module circuit design, support baud rate/control protocol automatic recognition, support software address code setting
- Imported precision motor, Response sensitivity, stable operation, low accuracy, no jitter under any speed

EX Marking




Certification



Markets



	Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80°C Db
	Ingress Protection level	IP68
PTZ function	Rotation range	Horizontal : 0~360° Vertical: : ±90°
	Rotation speed	Horizontal : 0.1°/S~40°/s Vertical: : 0.1°/S~40°/s
	monitoring location	300 locations can be set
	Communication method	RS485
	Board rate	2400 / 4800 / 9600 bps
	Communication protocol	PELCO – D、 PELCO – P etc.
	monitoring location setting accuracy	±0.1°
Other specifications	Temperature range	-40°C~60°C
	Relative humidity	≤ 95% (+25°C)
	Atmospheric pressure	80kpa~106 kpa
	Thermostat system	Optional
	Supply voltage	AC85V-260V
	Material	304 stainless steel (316, 316L for optional)
	Inlet hole specifications	G-3/4"x 1
	Inside dimension	Φ100*230mm for both
	Windows area	Φ65mm
	Electrical Connection	10-core composite cable
	Installation method	bracket or base installation